

BID SPECIFICATIONS HYDROSTATIC WALK BEHIND

SPECIFICATIONS

Engines – 23 hp Kawasaki, with oil filter and electric start; governed to 3600 rpm.
Air Filter – Heavy-duty canister air filtration system.
Drive System – Two Hydro-Gear 10cc variable displacement pumps powering two high-efficiency Parker/Ross wheel drive motors with 1.00" diameter tapered shafts.
Ground Speed – 0 to 6.7 mph (10.8 kmph) forward, 0 to 2.2 mph (3.5 kmph) reverse, infinitely variable.
Hydro Fluid – Synthetic oil.
Cutting Deck – 60", 10-gauge top that is formed and continuously seam-welded, with 10-gauge top reinforcement plate and 7-gauge side skirt. 7-gauge reinforcement rings at spindle assembly. 5.5" deep, 4-point suspension full-floating deck with six adjustable anti-scalp rollers.
Cutting Height – 1.5" to 4.5" in 0.5" increments.
Drive Tires – 18 x 8.50-8, 4-ply Turf Master.®
Caster Tires – Semi-Pneumatic 11 x 4.00-5, 4-ply smooth tread.
Casters – Double-yoke, caster wheel assembly.
Curb Weight – 751 lbs
Dimensions:
 60" Width
 Deflector Up61.4"
 Deflector Down72.2"
 All Units 45.0"
 Blades – 60" deck: 3-20.50" blades
 Blade-Tip Speed – Approximately 18,500 fpm.
 Blade Spindles – 1.75" diameter mounted in cast aluminum-alloy spindle housings with dual-sealed bearings. No maintenance required.
 Engine Deck – 7-gauge welded steel.
 Turning Radius – True zero-turn.
 Drive-Wheel Release – Allows wheel movement without engine running.
 Fuel Capacity – 5-gallon, single fuel tank.
 Electrical – 12-volt battery with 15-amp alternator.
 PTO Engagement – MagStop electromagnetic 200-ft-lbs clutch.
 Parking Brake – Standard.
 Hour Meter – Standard.
Safety Package – Operator Presence Controls (OPC). Operator must have speed control lever in neutral and blades disengaged to leave operator position without stopping engine.

Length
 With Deck, All Units 83.4"
Height

2008 Bid Specification Sheet